MT-4310W/MT-4310W-4G

Specification (Tablet only)	MT-4310W	MT-4310V	/-4G
Processor	Intel Cherry Trail x5-Z8350 Quad Core CPU, up to 1.92 GHz, 2M Cache		
OS Support	Windows 10 IoT 32 bit & 64 bit		
LCD	1280 x 800, 10.1" TFT LCD with LED backlight		
Brightness	400 nits		
Touch Input	True-flat PCAP touch with multi-touch support		
System Memory	DDR3 2 GB	LPDDR3 4 GB	
Storage Device	64 GB eMMC		
WiFi	Dual band 2.4 GHz/5.0 GHz, WiFi + BT; Optional 3G NGFF		
Camera	8MP AF rear facing camera		
Speaker/Audio + Mic	Yes/Yes		
Sensor	G sensor, light sensor		
I/O	microSD, micro-SIM, Power Jack, micro-USB		
Button	Power		
Battery	3.7V/4800 n	nAh, 17.76 Wh	
Physical Dimension (Tablet only)	I		
Dimension (W x D x H in mm)	260.7 x 16.8 x 175		
Weight (N. W. in g)	750		
Environmental			
Operating Condition	0°C - 50°C, 20%RH - 90%RH		
Storage Condition	-20°C - 70°C, 10%RH - 90%RH		
Dock Station			
Model Name	DS-220 DS-320	DS-200	DS-300
Serial Port	DB9 x 2		
Standard USB Port	USB 2.0 x 3		
LAN Port	GigaLan x 1		
CR Port	1		
Built-in Printer	3" WiFi (dual band) thermal printer (200 mm/sec max.)	N/A	
Tablet Charging	Yes		
Built-in Options	·		
Smart Card Reader	EMV level 2 certified (cannot co-exist with 4G/LTE module)		
3G Communication	N/A		
4G / LTE Communication	Selected bands for selected regions (cannot coexist with EMV Chip Card Reader)		
Attachment Options			
MSR (TA-220/TA-300)	3T MS	R reader	
RFID (TA-220)	Support MIFARE Classic 1K & MIFARE Ultralight		
Fingerprint sensor (TA-300)	Fingerprint Sensor (Active Capacitive technology)		
Pistol Grip (PG-201E)	Swappable battery module (5000 mAh); Optional 2D barcode scanner		
Pistol Grip (PG-500)	N/A		
Scanner	2D barcode scanner embedded in Pistol Grip		
Shoulder Strap + 2nd Battery Option (TA-500)	Swappable battery module (5000 mAh)		
Shoulder Strap + 2nd Battery Option (TA-600)		/Α	
Standalone Options	1		
Removal Battery Charging Rack (CS-100)	Charging rack for up	to 4 x removal battery	
	Single charging station for MT Series tablet		
Tablet Charging Rack (CS-210 / CS-220)	Single charging station	JII IUI IVII JEIIES LADIEL	
Quad Tablet Charging Rack (CS-200)		A	
	N Hand Strap is availa		

and Manufac

RoHS

8

Authorized Distributor / Reseller


Windows*



POSIFL

POSIFLEX TECHNOLOGY (INDIA) PVT. LTD. #7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavarapalya, Bengaluru, Karnataka 560093 Tel : +91 80 4078 2700 | Mob : +91 9535432110 Email : marketing@posiflexindia.com | www.posiflexindia.com

FC



The Best Companion for Mobile Retailing and Hospitality

MT-4310W/MT-4310W-4G

Ergonomic and Versatile Mobile POS



MT-4310W





Built-in 5000 mAh battery and optional 2D barcode scanner



Adoptable yet Durable

With durability to survive up to 1.2 meters drop, the MT-4310W Series is a rugged Windows tablet designed to meet any business applications.



Patented Pistol Grip (U.S. Patent 9436226 B2)

The optional patented pistol grip is ergonomically designed for easy carrying and houses a removable battery to vastly extend the overall operating time.



Multi-use Versatility

MT-4310W Series with the patented pistol grip are tailored for service on the go, suited for inventory, line busting, ticket taking, loyalty programs, and many more.



Transform with Dock Station

MT-4310W Series can transform into an all-in-one desktop POS terminal with the optional docking station that integrates a built-in 3" WiFi thermal printer.

ATTACHMENT



TA-220 Side attahcment of MSR and/or RFID



TA-300 Side attahcment of MSR and/or Fingerprint Sensor



TA-500 Additional 5000 mAh battery attachment for Hospitality Package with shoulder strap



CS-100 4 slots battery charger for charging up to RB-3000 battery x 4









CS-220 Single charging station with LAN port and USB2.0 x 2 port



DS-200 DS-300 Dock Staion with USB x 3, COM x 2, LAN and CR





Hand Strap Hand Strap is available for added security





PG-201E

Pistol Grip shaped handheld with 5000 mAh battery builtin and optional 2D barcode scanner for Retail Package





Dock Staion with 3" WiFi thermal printer, USB x 2, COM x 2, LAN and CR