



RP-326

Reliable Thermal Printer

- Paper Width : 79.5±0.5mm
- Printing Speed : 250mm(Max)/sec
- Resolution : 203dpi (8dot./mm)
- Interface : USB, Serial, Ethernet



Specification

Printing method	Direct thermal printing
Print width	72mm or 48mm
Resolution	203dpi
Printing speed	250mm/s
Printing density	576 dots/line or 384 dots/line
Character set	GB18030 (Simplified Chinese)
Print font	ASCII Font A: 12×24, ASCII Font B: 9×17, Chinese: 24×24
Character per line	Font A-48 lines/Font B-64 lines/Chinese-24 lines
Paper width	79.5±0.5mm
Paper roll diameter	80mm
Paper loading	Easy paper loading
Barcode type	UPCA/UPCE/EAN13/EAN8/CODE39/125/CodeBar/CODE128/CODE93/CODE11/MSI/QR CORE/PDF417
Auto cutter	1.5 million cuts
Interface	USB, Serial, Ethernet
Paper out detection function	Optional
Emulation	ESC/POS/OPOS
Driver	WIN2003/WINXP/WIN7/WIN8/WIN10/LINUX/Mac
Power supply	DC 24V, 2.5A
Cash drawer Control	DC 24V, 1A
Dimension (LxWxH)	191×140×143mm
Temperature	Working temperature: 0~45°C, Storage: -10~60°C
Humidity	Working temperature: 20 - 90%, Storage: 10 - 90% (paper excluded)