



TM-3010E

Secondary LCD Monitor

Specification	TM-3010E
LCD	9.7" TFT LCD
Resolution	Up to 1024 x 768
Touch	Bezel-free PCAP Touch
Interface	USB
System Supported	All XT Series
Power Supply	12V from Posiflex Terminal VGA port
Viewing Angle	60/70/70/70 degree (U/D/L/R)
Pixel Arrangement	RGB Vertical Stripe
Pixel Pitch	0.192 (H) x 0.192 (V)
Brightness	350 cd/m ²
Contrast Ratio	500:1
Display Interface	VGA
Response Time	20 ms (Raising + Falling)

Design and Manufacturing in Taiwan by Posiflex Technology, Inc.
The product information and specifications are subject to change without prior notice.
Please refer to the web site for more attachment options.

Certifications



V1.1_17042021

POSIFLEX

POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.

#7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavara Palaya, Bengaluru, Karnataka 560093
Tel : +91 80 4078 2700 | Mob : +91 9535432110
Email : marketing@posiflexindia.com | www.posiflexindia.com

Authorized Distributor / Reseller